

Safety Data Sheet CHLOROTETRAFLUOROETHANE (R124)

An Iwatani Company

www.advancedspecialtygases.com

Section 1: Product and Company Identification

Advanced Specialty Gases 135 Catron Dr. Reno, NV 89512

775-356-5500

IN CASE OF EMERGENCY CALL CHEMTREC: 1-800-424-9300

Product Code: CHLOROTETRAFLUOROETHANE (R124)

Section 2: Hazards Identification



Hazard Classification: Gases Under Pressure

Hazard Statements:

Contains gas under pressure; may explode if heated

Precautionary Statements

Storage:

Protect from sunlight.
Store in well-ventilated place.

Section 3: Composition/Information on Ingredients

CAS # 2837-89-0

Chemical Substance	Chemical Family	Trade Names
Chlorotetrafluoroethane	Refrigerants	HCFC-124, Ethane, 2-chloro-1,1,1,2-tetrafluoro-; CF3CHFCl; R 124 ,Forane (R124),1-chloro-1,2,2,2-tetrafluoroethane

Section 4: First Aid Measures

Skin Contact	Eye Contact	Ingestion	Inhalation	Note to Physicians
Flush skin with	Flush eyes with large amounts of water for at least 15	Unlikely route of	Move to fresh	Not available
water.	minutes	exposure	air	

Section 5: Fire Fighting Measures

Suitable Extinguishing Media	Products of Combustion	Protection of Firefighters
Nonflammable. Use appropriate media for type of surrounding fire. This material will become combustible when mixed with air under pressure and exposed to strong ignition sources.		 Wear self-contained, NIOSH- approved breathing apparatus

Section 6: Accidental Release Measures

Personal Precautions	Environmental Precautions	Methods for Containment
Always wear recommended personal protective equipment. Evacuate	Not available.	Stop leak if without risk and provide
area.		ventilation.

Methods for Cleanup	Other Information
Stop leak if possible without personal risk.	

Section 7: Handling and Storage

Handling	Storage
Store and use with adequate ventilation. Firmly secure cylinders upright to	Do not get liquid in eyes, on skin, or clothing. Protect cylinders
keep them from falling or being knocked over. Screw valve protection cap	from damage. Use a suitable hand truck to move cylinders; do not
firmly in place by hand. Store only where temperature will not exceed 125F	drag, roll, slide, or drop. Open valve slowly. Close cylinder valve
(52C). Store full and empty cylinders separately. Use a first-in, first-out	after each use; keep closed even when empty. If valve is hard to
inventory system to prevent storing full cylinders for long periods.	open, discontinue use and contact your supplier.

Section 8: Exposure Controls/Personal Protection

	Exposure Guidelines
ľ	AIHA WEEL (United States, 1/2009). TWA: 1000 ppm 8 hour(s).

Engineering Controls

No specific controls are needed.

Eye Protection	Skin Protection	Respiratory Protection
Wear safety glasses for normal	General work clothing and leather gloves would be	Wear self-contained, NIOSH-approved breathing
conditions	sufficient	apparatus

General Hygiene considerations

- Avoid breathing vapor or mist
- Avoid contact with eyes and skin
- Wash thoroughly after handling and before eating or drinking

Advanced Specialty Gases page 2 of 4
Generated by the SDS Manager from AsteRisk, LLC. All Rights Reserved Date of Preparation: 02/12/2025 13:40:26

Section 9: Physical and Chemical Properties

Physical State	Appearance	Color	Change in Appearance	Physical Form	Odor	Taste
Gas	Colorless	Clear	N/A	Gas	Faint ethereal odor	N/A

Flash Point	Flammability	Partition Coefficient	Autoignition Temperature	Upper Explosive Limits	Lower Explosive Limits
Not applicable	Not available	Not available	Not applicable	Not applicable	Not applicable

Boiling Point	Freezing Point	Vapor Pressure	Vapor Density	Specific Gravity	Water Solubility	рH	Odor Threshold	Evaporation Rate	Viscosity
-11C (12.2F)	-199C (- 326.2F)	49.1 psia @ 21.1 C (70 F)	4.74	1.34 @ 30C (86F)	Not available	Neutral	Not Available	>1 COMPARED TO: CCI4 = 1	Not available

Molecular Weight	Molecular Formula	Density	Weight per Gallon	Volatility by Volume	Volatility	Solvent Solubility
136.48 g/mole	C2-H-CI-F4	Not available	Not available	Not available	Not available	

Section 10: Stability and Reactivity

Stability Conditions to Avoid		Incompatible Materials
Stable under normal	Stable under normal	Freshly abraded aluminum surfaces. Chemically active metals: potassium, calcium,
conditions	conditions	powdered aluminum, magnesium and zinc

Hazardous Decomposition Products	Possibility of Hazardous Reactions	
Halogens halogen acids, and possibly carbonyl halides	Will not occur	

Section 11: Toxicology Information

Acute Effects

-	7 10 dito = 110 dito		
	Oral LD50	Dermal LD50	Inhalation
		LD30	
	LC50 : 4 hr. (rat) -	Not	Displaces oxygen in air and causes symptoms of asphyxiation. Including: loss of coordination, increases
	?360,000 ppm	Available	heart rate, deeper respiration. Severe exposure may cause cardiac arrhythmia.

Eye Irritation	Skin Irritation	Sensitization	
Frostbite, irritation	Irritation, frostbite	No health hazards classified.	

Chronic Effects

Carcinogenicity	Mutagenicity	Reproductive Effects	Developmental Effects
Not Available	Not Available	Not Available	No data

Section 12: Ecological Information

Fate and Transport

Eco toxicity	Persistence / Degradability	Bioaccumulation / Accumulation	Mobility in Environment
Fish toxicity: Not Available	Not Available	Low risk	Gas, so unlikely to remain in water.
Invertibrate toxicity: Not Available			
Algal toxicity: Not Available			
Phyto toxicity: Not Available			
Other toxicity: Not Available			

Section 13: Disposal Considerations

Disposal must comply with federal, state, and local disposal or discharge laws.

page 3 of 4

Date of Preparation: 02/12/2025 13:40:26

Section 14: Transportation Information

U.S. DOT 49 CFR 172.101

Proper Shipping Name	ID Number	Hazard Class or Division	Packing Group	Labeling Requirements	Passenger Aircraft or Railcar Quantity Limitations	Cargo Aircraft Only Quantity Limitations	Additional Shipping Description
1-Chloro-1,2,2,2- tetrafluoroethane	UN1021	2.2	Not required	N/a	N/A	N/A	N/A

Canadian Transportation of Dangerous Goods

Shipping Name		N Number	Class	Packing Group / Risk Group
1-Chloro-1,2,2,2-tetraflu	oroethane UN	N1021	2.2	Not required

Section 15: Regulatory Information

U.S. Regulations

CERCLA Sections	SARA 355.30	SARA 355.40	
Not regulated	Not available	Not available	

SARA 370.21

Acute	Chronic	Fire	Reactive	Sudden Release
Yes	No	No	No	Yes

SARA 372.65

Not regulated

OSHA Process Safety

Not regulated

State Regulations

CA Proposition 65
Not regulated

Canadian Regulations

WHMIS Classification
Not available

National Inventory Status

I	US Inventory (TSCA)	TSCA 12b Export Notification	Canada Inventory (DSL/NDSL)	
	Not available	Not available	Not available	

Section 16: Other Information

NFPA Rating

Health - 2, Flammability - 0, Reactivity - 0

0 = minimal hazard, 1 = slight hazard, 2 = moderate hazard, 3 = severe hazard, 4 = extreme hazard